

Unimax 1010

P/N: 543-12310-00



The one with temperature-control and a maximum loading capacity of 5 kg

This shaker can be integrated into the modular incubation system, and it is therefore ideal for all temperature-controlled shaking tasks. In addition, it is possible to operate several shakers of this size in one climate chamber. We recommend climate chambers made by Memmert.

With a speed range of 30-500 rpm and an orbit of 10 mm, samples are optimally kept in motion. Time-dependent applications can be performed without any problems by using the timer (max. 999 min).

Unimax 1010 - Technical Data

| | |
|--------------------------------|--|
| Overheat protection | self-resetting |
| Permissible ambient conditions | 5 - 31 °C at 80 % rel. humidity 32 - 40 °C decreasing linearly up to max. 50 % rel. humidity |
| Weight | 8 kg |
| Protection class IEC 60529 | IP 40 |
| Timer | yes (max. 999 min) |
| Rotation speed range | 30 - 500 rpm |
| Power input | 50 W |
| Dimensions (w/d/h) | 320 x 375 x 125 mm |
| Max. Load | 5 kg |
| Operating Mode | timer or continuous |
| Rotation speed setting | digital |
| Orbit / Stroke | 10 mm |
| Platform size | 290 x 258 mm |
| Accessories included | non-skid rubber mat |
| Angle | - |
| Motion | orbital |